



HAHN - Elektrobau GmbH & Co. KG

Bellersheimerstraße 45
35410 Hungen
Germany

phone: +49 (0) 6402/808-0
fax: +49 (0) 6402/808-60
email: info@hahn-trafo.de

Data sheet: BV EI 481 1172


Frame size/Core height	Output (ta 70B)	h 1 (mm)	h 2 (mm)	weight kg
EI 481 / 16,8 mm	10 VA	27,9 ± 0,5	34,6 ± 0,5	0,300

- Test certifications to ENEC 10- and VDE-regulations
- non short-circuit-proof at temperature class ta 70 °C/B
- type "K" cast housing with 2 fixing straps
- maximum safety and long-term durability
- excellent temperature fluctuation resistance properties
- minimum size, maximum capacity
- Self-extinguishing cast housing and sealing material
- individually tested with certificate

Article no. BV	Output ta 70°C/B	prim.V	Connecting pins	Operating point sec. ± 5%	Connecting pins	No-load voltage V ± 5%
EI 481 1172	10	230	1-6	1 x 12V 1111 mA	8 - 11	1 x 9.8

**Primary protection by means of transformer heat coils to IEC 127 Standards or
secondarily with PTC resistances.**

Certificates



Dimensions of drawing without tolerances ± 0,3 mm.