



SS32A THRU SS310A

3.0AMP.SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

Voltage Range
20 to 100 Volts
Current
3.0Amperes


Features

- For surface mounted application
- Easy pick and place
- Metal to silicon rectifier, majority carrier conduction
- Low power loss, high efficiency
- High current capability, low VF
- High surge current capability
- Plastic material used carriers Underwriters Laboratory Classification 94V-0
- Epitaxial construction
- High temperature soldering:
260°C / 10 seconds at terminals

Mechanical Data

- Case: molded plastic
- Terminals:Solder plated
- Polarity:Indicated by cathode band
- Packaging:12mm tape EIA STD RS-481
- Weight:0.064gram

SMA



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave,60Hz,resistive or inductive load.

For capacitive load,derate current by 20%

Type Number		SS 32A	SS 33A	SS 34A	SS 35A	SS 36A	SS 39A	SS 310A	UNITS
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	90	100	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	63	70	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	90	100	V
Maximum Average Forward Rectified Current @T _L =100 °C	I _{F(AV)}	3.0						A	
Peak Forward Surge Current,8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	80						A	
Maximum Instantaneous Forward Voltage (Note@1.0 A)	V _F	0.45	0.55	0.60	0.70	0.85			V
Maximum DC Reverse Current @ T _A =25°C At Rated DC Blocking Voltage @ T _A =125°C	I _R	1.0 20.0						mA	
Typical Thermal Resistance (Note 1) (Note 2)	R _{θ JL} R _{θ JA}	10 50						°C /W	
Operating Junction Temperature Range	T _J	-55 to +150						°C	
Storage Temperature Range	T _{STG}	-55 to +175						°C	

NOTES: 1. Thermal resistance junction to lead.
2. Thermal resistance junction to ambient.

RATING AND CHARACTERISTIC CURVES

SS32A THRU SS310A



FIG.1-MAXIMUM NONO-REPETITIVE FORWARD SURGE CURRENT PER BRIDGE ELEMENT




FIG.2-MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER BRIDGE ELEMENT




FIG.4-TYPICAL REVERSE CHARACTERISTICS PER BRIDGE ELEMENT

