

Small Signal Product

Hermetically Sealed Glass Zener

FEATURES

- Wide zener voltage range selection: 2.0V to 75V
- Compression bonded construction
- Hermetically sealed glass
- Solder hot dip Tin(Sn) lead finish
- Pb free and RoHS compliant
- All external surfaces are corrosion resistant and leads are readily solderable



DO-35

Hermetically Sealed Glass



MECHANICAL DATA

- Case: DO-35
- High temperature soldering guaranteed: 260°C/10s
- Polarity: Cathode indicated by polarity band

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation	P _D	500	mW
Forward Voltage I _F = 100 mA	V _F	1	V
Junction and Storage Temperature Range	T _J , T _{STG}	- 65 to +200	°C

These ratings are limiting values above which the serviceability of the diode may be impaired.

Small Signal Product

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Device Type	$V_Z @ I_{ZT}$ (V)		I_{ZT} (mA)	$Z_{ZT} @ I_{ZT}$ (Ω) Max	I_{ZK} (mA)	$Z_{ZK} @ I_{ZK}$ (Ω) Max	$I_R @ V_R$ (μA) Max	V_R (V)
	Min	Max						
BZX55C2V0	1.88	2.11	5.0	100	1.0	600	100	1.0
BZX55C2V2	2.08	2.33	5.0	100	1.0	600	100	1.0
BZX55C2V4	2.28	2.56	5.0	85	1.0	600	50	1.0
BZX55C2V7	2.51	2.89	5.0	85	1.0	600	10	1.0
BZX55C3V0	2.8	3.2	5.0	85	1.0	600	4.0	1.0
BZX55C3V3	3.1	3.5	5.0	85	1.0	600	2.0	1.0
BZX55C3V6	3.4	3.8	5.0	85	1.0	600	2.0	1.0
BZX55C3V9	3.7	4.1	5.0	85	1.0	600	2.0	1.0
BZX55C4V3	4.0	4.6	5.0	75	1.0	600	1.0	1.0
BZX55C4V7	4.4	5.0	5.0	60	1.0	600	0.5	1.0
BZX55C5V1	4.8	5.4	5.0	35	1.0	550	0.1	1.0
BZX55C5V6	5.2	6.0	5.0	25	1.0	450	0.1	1.0
BZX55C6V2	5.8	6.6	5.0	10	1.0	200	0.1	2.0
BZX55C6V8	6.4	7.2	5.0	8	1.0	150	0.1	3.0
BZX55C7V5	7.0	7.9	5.0	7	1.0	50	0.1	5.0
BZX55C8V2	7.7	8.7	5.0	7	1.0	50	0.1	6.2
BZX55C9V1	8.5	9.6	5.0	10	1.0	50	0.1	6.8
BZX55C10	9.4	10.6	5.0	15	1.0	70	0.1	7.5
BZX55C11	10.4	11.6	5.0	20	1.0	70	0.1	8.2
BZX55C12	11.4	12.7	5.0	20	1.0	90	0.1	9.1
BZX55C13	12.4	14.1	5.0	26	1.0	110	0.1	10
BZX55C15	13.8	15.6	5.0	30	1.0	110	0.1	11
BZX55C16	15.3	17.1	5.0	40	1.0	170	0.1	12
BZX55C18	16.8	19.1	5.0	50	1.0	170	0.1	14
BZX55C20	18.8	21.2	5.0	55	1.0	220	0.1	15
BZX55C22	20.8	23.3	5.0	55	1.0	220	0.1	17
BZX55C24	22.8	25.6	5.0	80	1.0	220	0.1	18
BZX55C27	25.1	28.9	5.0	80	1.0	220	0.1	20
BZX55C30	28	32	5.0	80	1.0	220	0.1	22
BZX55C33	31	35	5.0	80	1.0	220	0.1	24
BZX55C36	34	38	5.0	80	1.0	220	0.1	27
BZX55C39	37	41	2.5	90	0.5	500	0.1	28
BZX55C43	40	46	2.5	90	0.5	600	0.1	32
BZX55C47	44	50	2.5	110	0.5	700	0.1	35
BZX55C51	48	54	2.5	125	0.5	700	0.1	38
BZX55C56	52	60	2.5	135	0.5	1000	0.1	42
BZX55C62	58	66	2.5	150	0.5	1000	0.1	47
BZX55C68	64	72	2.5	160	0.5	1000	0.1	51
BZX55C75	70	80	2.5	170	0.5	1000	0.1	56

Notes : 1. Tolerance and voltage designation : the type numbers listed have zener voltage as shown.

2. Specials available include : nominal zener voltages between the voltages shown and tighter voltage, for detailed information on price, availability and delivery, contact your nearest Taiwan Semiconductor representative.

3. Zener voltage (V_Z) measurement : the zener voltage is measured under pulse conditions such that T_J is more than 2°C above T_A .

4. Zener impedance (Z_Z) derivation : zener impedance is derived from the 60-cycle ac voltage, which results when ac current having an RMS value equal to 10% of the dc zener current (I_{ZT}) is superimposed to I_{ZT} .

Small Signal Product
ORDERING INFORMATION


PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING
BZX55Cxxx (Note1)	(Note 2)	R0	G	DO-35	10K / 14" Reel
		A0			5K / Box (Ammo)

Note 1: "xxx" defines voltage from 2.0V (BZX55C2V0) to 75V (BZX55C75)

Note 2: Manufacture special control, if empty means no special control requirement.

EXAMPLE

PREFERRED P/N	PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
BZX55C75 R0G	BZX55C75		R0	G	Green compound
BZX55C75-L0 R0G	BZX55C75	L0	R0	G	Green compound
BZX55C75-B0 R0G	BZX55C75	B0	R0	G	Green compound

PACKAGE OUTLINE DIMENSION


DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	0.34	0.60	0.013	0.024
B	2.90	5.08	0.114	0.200
C	25.40	38.10	1.000	1.500
D	1.30	2.28	0.051	0.090

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.